

**TECHNICAL DATA SHEET****Product Code: (GLS-GP-12)****ADS Glass & Ceramic Glow Paint-12****Applications:** Glass Surfaces Interior and Exterior.**Method of Use:** Brush, Roller & Spray.**Glow Period:** 10-12<sup>+</sup> hours after charging according to color used.

**Product Specifications:** High Quality Self-Illumination Water-based paint, Eco-Friendly and according to international standards with long lasting properties & excellent weather resistance, water resistance, water repellent properties , with very low dirt pick-up property. It adds richness of the base coat and creates an artistic matt or silky antique effects with ancient elegant look and excellent adhesion Properties, which glow in the dark without any source of energy as it stores energy from any light sources to lasts illuminate from 6 up to 12 hours depending on the type & Color of product used & the intensity of the darkness.

**Thinner:** Water.**Thinner (Volume):**10-20% depending on method of application**How to Use:**

1. Clean the surface from any dust very well.
2. Must blend well (3 - 5) minutes before use and make sure that there is no residue in the bottom of the package.
3. Add Thinner by volume of 10-20% and mix well.
4. Airless spray requirements: Pressure: 3-4 bar (3000-4000psi) - **Nozzle Size: 3.0-3.5**
5. Apply several layers (1-4 layers) with an interval of about 20-30 minutes between layer & the other.
6. Oven use is must.
7. You must save the package at room temperature 0-30 degrees Celsius.
8. Advised to paint at a temperature of between 5 and 30 degrees Celsius.
9. The storage and transportation of the product must be in the original containers.

**TECHNICAL DATA SHEET**

**Product Code: (GLS-GP-12)**

**ADS Glass & Ceramic Glow Paint-12**

**10. Approximately 1 liter can cover about 7 to 9 square meters as one layer depends on the type of surface and application method.**

**11. Keep away from children.**

**Touch Dry: 30-45 min**

**Dry Time: 3-4 hours**

**Hard Dry: 24 hours**

**(Temperature, humidity, air movement, film thickness and number of coats all affect the drying time).**

**Shelf Life: 18 months, in original sealed container, with proper storage conditions.**

**Health & Safety:**

- As a general rule, avoid skin and eye contact by wearing overalls, gloves, goggles, and mask etc.
- Spillage on skin should immediately be removed by thorough washing with water and soap or suitable cleaner.
- Eye should be flushed with fresh water
- Avoid inhalation of vapors and paint mist by wearing suitable mas
- In the event of ingestion and eye contact, seek medical attention immediately.
- Painting must be carried out in well-ventilated area.
- This product contains flammable materials and should be kept away from the sparks and open flames.
- Smoking in the area should not be permitted.
- Local safety regulations should be followed.